



Coilheater

Unevenly wound to give a more even heat supply along the bushings length. Without built-in thermocouple. Voltage 230 V. Each heater is separately tested when produced to ensure high quality. The dimension of the resistanc wire is made so it will not be damaged even if the heater is used with maximum power constantly.

The length can be adjusted if needed by pulling the heater.

Part No.	$\varnothing D/mm$	$\varnothing D1/mm$	L/mm	Wattage/W
CS14120330200	12.3	16.7	33	200
CS14120430200	12.3	16.7	43	200
CS14120530225	12.3	16.7	53	225
CS14120730250	12.3	16.7	73	250
CS14120930350	12.3	16.7	93	350
CS14121130350	12.3	16.7	113	350
CS14150310260	15.3	19.7	31	260
CS14150510300	15.3	19.7	51	300
CS14150710350	15.3	19.7	71	350
CS14150910450	15.3	19.7	91	450
CS14151110450	15.3	19.7	111	450
CS14151310500	15.3	19.7	131	500
CS14151510550	15.3	19.7	151	550
CS14210330300	21.3	25.7	33	300
CS14210490400	21.3	25.7	49	400
CS14210690450	21.3	25.7	69	450
CS14210890500	21.3	25.7	89	500
CS14211090600	21.3	25.7	109	600
CS14211290650	21.3	25.7	129	650
CS14211490700	21.3	25.7	149	700
CS14211690750	21.3	25.7	169	750
CS01280520500	28.3	33.7	52	500
CS01280680600	28.3	33.7	68	600
CS01280880700	28.3	33.7	88	700
CS01281080750	28.3	33.7	108	750
CS01281280800	28.3	33.7	128	800
CS01281480850	28.3	33.7	148	850
CS01281680900	28.3	33.7	168	900
CS01281880950	28.3	33.7	188	950